



MATERIAL SAFETY DATA SHEET

DATE OF ISSUE: 02/05/2011

Section 1: IDENTIFICATION OF THE MATERIAL & SUPPLIER

PRODUCT IDENTIFICATION: Railway Track Signal 24/15/1

COMPANY: Howard & Sons Pyrotechnics (Manufacturing) Pty. Ltd.
ADDRESS: Portland Road Wallerawang, New South Wales, 2845, Australia
TELEPHONE: (02) 6355 7301
EMERGENCY TELEPHONE NUMBERS: 0418 218 432 or 0419 270 535
POISON INFORMATION: 13 11 26 **IF RELEASED:** CALL 000

Section 2: HAZARDS IDENTIFICATION

PRODUCT NAME: Pyrotechnic Safety Device **OTHER NAME: Railway Track Signal 24/15/1**
(Pyrotechnic)
HAZARD CLASSIFICATION: DANGEROUS GOODS, Non hazardous substance as per
(NOHSC 1008:2004)
PRODUCT CODE: DETVIC **USE:** Audible Warning device
UN NUMBER: 0193 **DANGEROUS GOODS CLASS AND SUB RISK:** 1.4S
HAZCHEM CODE: E **POISONS SCHEDULE:** None Allocated
PACKING GROUP: S **SUBSIDIARY RISK:**
STABILITY & REACTIVITY: This product is stable and non-reactive.
Avoid transporting with strong acids or alkalies keep dry keep away from flame or excessive heat.
Hazardous Polymerization will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of sulfur & nitrogen gasses produced in use

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL ENTITY	CAS NUMBER	PROPORTION
Potassium Chlorate	3811-04-0	HIGH
Sulphur	7704-34-9	HIGH
Silica Sand	-----	MED
Poly Vinyl Acetate	9003-20-7	VLOW
Guar Gum	9000-30-0	VLOW =100%

PROPORTION (% weight per weight) :
VHIGH > 60, HIGH 30-60, MED 10 - 29, LOW 1 - 9, VLOW <1

TECHNICAL SPECIFICATIONS:

Effect Description	Emits an audible report in excess of 150 decibels						
Case dimensions	50 MM DIA X 10 MM thick			Internal Diameter		NA	
Effect Height	NA	Effect Width	NA	Burn Time	Instant		
Plastic Weight	3 gms	Paper Weight	NA	Clay Weight	NA	Fuse Head	NA
NEQ Star	NA	NEQ Inserts	NA	NEQ B/Pdr	NA	NEQ COMP	10 gms
NEQ/Total	10 gms	Total Gross weight of Product:			13 gms		
Sub Box Size	NA	Cannisters Per Carton		50	Carton Size CMB		0.028
Carton Dimensions	31 x 31 x 30 cms		Packing	12\1	Sub Box Weight Net		NA
Cannister weight Net	40 gms	Carton Weight Net		1.8kgs	Carton Weight Gross		11 kgs
Firing Controls	Initiated by the extreme pressure inherent between a locomotive wheel and the track.						
Set Up	Place non slip green face on track face.						
	Ensuring that the wire assembly part of the Railway Track signal is facing in the						
	direction of approaching rolling stock, unfurl the aluminium wire attached and wrap it						
	around and into the profile sides of the track						

Section 4: FIRST AID MEASURES

Eye: If this chemical contacts the eyes, immediately wash (irrigate) the eyes with large amounts of water, occasionally lifting the lower and upper lids. Get medical attention immediately.

Skin: If this chemical contacts this skin, immediately wash the contaminated skin with water. If this chemical penetrates the clothing, immediately remove the clothing and wash the skin with water. If symptoms occur after washing, get medical attention immediately

Breath: If a person breathes large amounts of this chemical, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

Swallow: If this chemical has been swallowed, get medical attention immediately.

Section 5: FIRE FIGHTING MEASURES

Provide access to fire extinguisher at all times. Extinguisher must comply with relevant classification.

HAZCHEM CODE: E **EXTIGUISHING MEDIA:** Water **SPECIFIC HAZARD:** Very Loud Instant Report

DO NOT USE POWDER OR Co2 FIRE EXTINGUISHERS.

HAZARDS FROM COMBUSTION PRODUCTS: Hazardous Polymerization will not occur. Hazardous Decomposition Products: Oxides of sulfur & nitrogen gasses produced in use

DO NOT FIGHT EXPLOSIVE FIRES

CONSULT THE EMERGENCY PROCEEDURE GUIDE TRAVELLING WITH THIS PRODUCT FOR FIRE SITE SPECIFIC FIRE FIGHTING PROCEDURES AND EVACUATION DISTANCES.

Section 6: ACCIDENTAL RELEASE MEASURES

In case of spillage, dampen powders with water. Sweep up any powders using natural fibre brushes and non ferrous dust pans not steel, or any material that could produce sparks or present a risk of static discharge.

Also please refer to the **Emergency Procedure Guide** supplied with the Shipping Document by the freighter. This will detail safety distances based upon the entire load on-site, providing the Net Explosive Quantity (kg) and Class/UN of the total product.

It will provide further safety measures relating to the total product.

Section 7: HANDLING & STORAGE

STORAGE: Lighters, matches, open flame or other source of ignition, or volatile materials are not allowed within 16m of any magazine.

DO NOT make any repairs to the inside or outside of a magazine containing any explosive material. ALWAYS be sure magazines are solidly built and securely locked, in accordance with federal regulations, to protect the explosive materials from weather, fire and theft. Keep insides of magazines clean, dry, cool and well ventilated.

TRANSPORT: **Class 1.4S. UN Number 0193.** Transport as per Section 8 of the Australian Dangerous Goods Code. Keep Dry. NEVER ship explosive materials in any packaging except their original packaging or alternate approved packaging provided by the manufacturer. Load and unload explosive materials carefully.

DOCUMENTATION: As per Section 4 of the Australian Dangerous Goods Code.

Clean up spills of explosive materials promptly. Create a containment zone until the hazard has been removed.

FIRE/EXPLOSION HAZARD:

NEVER;

1. Expose explosive materials to flame, excessive heat, sparks, friction or impact.
2. Fight fires when explosive materials are involved. Remove all personnel to a safe location immediately and guard area against intruders.
3. Take apart, or in any way, investigate the contents of any explosive device or detonator.
4. Use any explosive materials unless completely familiar with the safe and correct procedures for their use.
5. use explosive materials that have been water soaked, even if they now appear to be dried out.

ALWAYS remember you are handling explosive materials. Use reasonable care to protect the explosive materials from extremes of heat, friction or shock. ALWAYS keep explosives locked up.

Pyrotechnic substance capable of burning with intense heat. Produces oxides of Sulphur, Carbon, Nitrogen and metal slag.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Not relevant in packaged form.

EXPOSURE STANDARDS: Not relevant.

ENGINEERING CONTROLS: N/A

IN USE

THIS PRODUCT IS FOR OUTDOOR USE ONLY. INITIATION BY EXTREME COMPRESSION ONLY

THIS PRODUCT HAS A MINIMUM SAFETY DISTANCE TO PERSONNEL OF 10 MTRS SECURE TO RAILWAY TRACK AS PER SET UP INSTRUCTIONS ABOVE.

READ IN CONJUNCTION WITH THE ATTACHED INSTALLATION DIAGRAMS.

RELEVANT HEALTH HAZARD INFORMATION: Follow Section 4 for First Aid procedures.

- It is not recommended to allow contact with skin or eyes.
- Do not breathe in large amounts of the substance.
- Do not swallow any amount of this substance.

Section 9: PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE: Orange and Green flat cylindrical case 50mm in diameter and 10mm thick with wire attached

BOILING POINT / MELTING POINT: N / A FLASH POINT (C): N / A

VAPOUR PRESSURE: N / A FLAMMABILITY LIMITS (%): N / A

SPECIFIC GRAVITY: N / A SOLUBILITY IN WATER (g/L): < 65%

Section 10: STABILITY & REACTIVITY

EXPOSURE STANDARDS:

This product is stable and non reactive.

SHELF LIFE:

**If stored in dry, cool conditions 5 years from manufacture date.
The manufacture date is stamped on the rear of the RTS case**

NEVER use explosive materials that show any sign of deterioration

NEVER expose explosive materials to extreme sources of heat or to open flame, UNLESS the manufacturer has recommended such materials or procedures for their use.

NEVER subject explosive materials to excessive impact or friction.

Section 11: TOXICOLOGICAL INFORMATION

Oral LD₅₀ (Rats):>5050 mg/kg body weight

Dermal LD₅₀ (Rats):>2020 mg/kg body weight

Inhalation @ 90% LC₅₀ (Rats):>5.49 mg/L air concentration

Skin Effects (Rabbits): Slightly irritating

Eye Effects (Rabbits): Minimal irritation in non-washed eyes

CARCINOGENICITY, TERATOGENICITY, MUTAGENICITY:

This product does not contain any ingredient designated by IARC, or NOHSC as a probable human carcinogen.

Do not eat or swallow. Ensure adequate ventilation.

ALWAYS remain clear of the detonation area until post-blast fumes, dusts, or smoke has subsided.

NEVER breathe dust or vapours from explosive materials.

ALWAYS remain clear of the detonation area until post-blast fumes, dusts, or smoke has subsided.

NEVER breathe dust or vapours from explosive materials.

Section 12: ECOLOGICAL INFORMATION

Dispose of all debris responsibly. Clean up surrounding area using a rake & collect any remaining debris.

Ecotoxicity: Raw materials are toxic to flora & fauna. Final product casing greatly reduces risk to the environment and wildlife.

Provided that the products case can be determined as free from explosives by a licensed pyrotechnician, the spent cases can go to licensed landfill.

Section 13: DISPOSAL CONSIDERATIONS

TO DISPOSE OF UNFIRED PYROTECHNIC PRODUCT CONTACT YOUR SUPPLIER

Disposal of unfired product should only be carried out by a licensed pyrotechnic waste disposal contractor

Contact Howard & Sons Pyrotechnics on 02) 6355 7301

ALWAYS dispose of explosive materials by shipping them to an approved disposal agency. Packaging, marking, labelling and transporting must be in accordance with regulations. NEVER ship explosive materials in any packaging except their original packaging or alternate approved packaging provided by the manufacturer.

Special conditions and instructions may apply. Specific guidance should be obtained from the manufacturer.

NEVER leave explosive materials or packaging materials where children, unauthorized persons or livestock can get to them.

NEVER allow any packaging materials to be burned in a confined space or to be reused.

When returning explosives to the manufacturer contact for approval prior to shipment.

Section 14: TRANSPORT INFORMATION

UN number: **0193**

UN Shipping name: **Railway Track Signals**

Class: **1.4S**

Dangerous Goods Packing Group: **II**

Hazchem Code: **E**

Further Precautions for user:

Ensure the correct documentation is present-

- 1.4S Emergency Procedure Guide
- Shipping Documents as per Section 4 of the Australian Dangerous Goods Code.
- Transport as per Section 8 of the Australian Dangerous Goods Code. Keep Dry.
- Pyrotechnics must travel within their original UN approved packaging

Section 15: REGULATORY INFORMATION

It is a regulation in every state or territory in Australia that a license is required to purchase, keep and use this product. It is a requirement in every state and territory in Australia that notification be made to the Police, Fire services, Safety authorities and in some cases Air services, of any intended display using display pyrotechnics. Consult Australian Standard 2187.1/2/3/4 for further information.

Section 16: OTHER INFORMATION

LICENCING REQUIREMENTS:

As the seller Howard & Sons Pyrotechnics must comply with State and National Law when supplying explosive product to clients. As a rule, the sale must comply with the State Law licencing requirements of the receiver. Further, Howard & Sons must maintain NSW WorkCover requirements when processing, dispatching, and completing a sale.

UNSUPERVISED HANDLING LICENCE: *An Unsupervised Handling Licence does not authorise the holder to purchase or possess explosives and/or dangerous goods in their own right.*

This form is used to apply for an Unsupervised Handling Licence. An Unsupervised Handling Licence entitles the licence holder, if nominated on a security plan, to handle explosives and/or security sensitive dangerous substances without supervision subject to the licensee working under the direction and control of a person licensed to be in possession of explosives and/or security sensitive dangerous substances; the handling of the explosives or security sensitive dangerous substances is of a type and manner authorised under the supervisor's licence and the holder of the Unsupervised Handling licence complies with any conditions of the supervisor's licence. (NSW Explosives Act 2003, NSW Explosives Regulation 2005. Application form FE01)

Date of MSDS preparation: 02/05/2011

Although this information is presented in good faith and compiled from various sources, believed to be accurate, Howard & Sons Pyrotechnics (Manufacturing) Pty. Ltd. make no representations or warrant as to the completeness or accuracy there of.

As the products performance and suitability depends on various factors, the purchasers of our products should determine for themselves whether the product is suitable for their particular use.

WARNING: All explosive materials are dangerous and must be handled and used with care either by or under the direction of competent, experienced persons. All commercial explosive materials are designed to detonate when supplied with a sufficient amount of initiating energy. Explosive materials cannot differentiate between initiating energy purposely supplied or accidentally supplied. It is the responsibility of all persons who handle explosive materials to know and follow all approved safety procedures. This responsibility includes the necessity of being familiar with, and observing federal, state, and local rules and regulations governing explosive materials.

If after careful reading this MSDS, you have any questions or doubts as to how to use these products - DO NOT USE THEM - consult the manufacturer for additional information.

CONTACT POINT:	Howard & Sons Pyrotechnics (Manufacturing) Pty. Ltd.
	Technical Manager CHRISTIAN HOWARD
	Telephone Number: WH: (02) 6355 7301 AH: 0418 218 432

Although this information is presented in good faith and compiled from various sources, believed to be accurate, Howard & Sons Pyrotechnics (Manufacturing) Pty. Ltd. make no representations or warrant as to the completeness or accuracy thereof.

As the products performance and suitability depends on various factors, the purchasers of our products should determine for themselves whether the product is suitable for their particular use.